

# COLOR REFLECTION DENSITOMETER

R  
7  
1  
0



- Density
- Density Difference

IHARA

# R710 COLOR REFLECTION DENSITOMETER

## HIGH PERFORMANCE & RELIABILITY

Ihara Electronic Industries utilizes advanced microcomputer technology to ensure superior performance and reliability for its entire line of densitometric products. Standard functions include: *density and density difference*.

## MENU DRIVEN COMMANDS

Simply select the functions desired. No memorization or operation manual required.

## SELF-GUIDING PROMPTS

Clear and concise instructions are prompted across the large graphic LCD display in every measurement.

## HELP KEY PROVIDES EXPLANATION OF KEY FUNCTIONS

Detailed explanations are available for all measurement functions along with answers to frequently asked questions.

## QUICK CALIBRATION

It takes seconds to calibrate using the quick calibration function. Standard calibration is also available.

## LARGE GRAPHIC LCD DISPLAY

The easy to read graphic LCD display allows the user to determine the precise configuration desired, including right or left handed view, two or three decimal precision and display options.

## PRINTER AND COMPUTER INTERFACE

The configurable RS-232C serial interface is capable of linking the R710 to a computer or to the IHARA PR-95 printer.

## SECURITY USER CODE (OPTIONAL)

As an option to safeguard your investment, the R710 may be set to operate only with the correct user code.



## IHARA R710 COLOR REFLECTION DENSITOMETER SPECIFICATIONS

### • MEASUREMENT FUNCTIONS

Density  
Density Difference

### • FILTER RESPONSE

Status T  
Status E  
Status A

### • MEASURING GEOMETRY

0°/45° (ANSI PH2.17, ISO 5/4,  
DIN 16536)

### • MEASURING RANGE

Density 0.00D - 2.50D

### • REPEATABILITY

± 0.01D

### • ACCURACY

± 0.02D

### • LIGHT SOURCE

Halogen Lamp, Approximately 2856°K

### • APERTURE DIAMETER

3.0mm (1.7mm optional)

### • DETECTOR

GaAsP Photodiode

### • DISPLAY

128 x 64 Dot Graphic LCD

### • POWER SUPPLY

Ni-Cad (4.8V), 800mAh

### • RECHARGE TIME

Approximately 1.5 hours

### • MEASUREMENTS PER CHARGE

Approximately 4,000 (Internal Testing)

### • WARM UP TIME

None

### • MEASURING TIME

Approximately 1 second

### • OPERATING TEMPERATURE RANGE

41°F ~ 104°F (5°C ~ 40°C)

### • POLARIZATION FILTER

(Optional)

### • SECURITY USER CODE

(Optional)

### • DIMENSIONS

2 3/4"W x 2"H x 8 1/4"L  
(72mm x 50mm x 210mm)

### • WEIGHT

1.2 lbs. (With Batteries)  
(530 g)

### • COMPUTER OUTPUT

Configurable RS-232C Serial Interface

### • ACCESSORIES

Operation Manual  
Calibration Standard  
AC Adapter (9V, 500mA, center-negative)  
Carrying Case  
Serial Interface Cable (Optional)  
Ihara PR-95 Printer (Optional)  
Software (Optional)  
Cable Harness (Optional)

Specifications subject to change without notice. Printed in USA • Form R710-CT (04/98)

# IHARA

Ihara U.S., Inc.  
25030 Avenue Tibbitts, Building K  
Valencia, California 91355-9877 USA  
Tel: 661-257-5772  
Fax: 661-257-5880  
www.iharus.com

#### World Headquarters:

Ihara Electronic Industries Co., Ltd.  
2077 Kamitaraga-Cho  
Kasugai City, Aichi 486 Japan  
Tel: 0568-81-6824  
Fax: 0568-81-6040  
www.ihara-group.com

#### Sales Office:

0568-76-7878 (Japan)  
661-257-5772  
(For all other countries)